

FLEETWOOD WINDOWS & DOORS TEST REPORT

SCOPE OF WORK

AAMA/WDMA/CSA 101/I.S.2/A440 TESTING ON THEIR SERIES 4070 – T HP SLIDING GLASS
DOOR – SLIDING DOOR

REPORT NUMBER

S0187.02-303-44 R1

TEST DATES

02/20/25 - 03/03/25

ISSUE DATE

03/06/25

REVISED DATE

03/14/25


PAGES

16

DOCUMENT CONTROL NUMBER

RT-R-AMER-Test-2804 (06/21/24)

© 2017 INTERTEK



TEST REPORT FOR FLEETWOOD WINDOWS & DOORS

Report No.: S0187.02-303-44 R1

Date: 03/06/25

REPORT ISSUED TO

FLEETWOOD WINDOWS & DOORS

1 Fleetwood Way

Corona, CA 92879

SECTION 1

SCOPE

Architectural Testing, Inc. (an Intertek company) dba Intertek Building & Construction (B&C) was contracted by Fleetwood Windows & Doors – 1 Fleetwood Way Corona, CA 92879 to perform testing in accordance with AAMA/WDMA/CSA 101/I.S.2/A440 on their Series 4070 – T HP Sliding Glass Door – Sliding Door. Results obtained are tested values and were secured by using the designated test methods. Testing was conducted at the Intertek Inc. test facility in Lake Forest, CA.

This report does not constitute certification of this product nor an opinion or endorsement by this laboratory. Intertek B&C will service this report for the entire test record retention period. The test record retention period ends four years after the test date. Test records, such as detailed drawings, datasheets, or other pertinent project documentation, will be retained for the entire test record retention period.

Unless differently required, Intertek reports apply the "Simple Acceptance" rule, also called "Shared Risk approach," of ILAC-G8:09/2019, Guidelines on Decision Rules and Statements of Conformity.

For INTERTEK B&C:

COMPLETED BY:	Benjamin Johns	REVIEWED BY:	Tyler Westerling P. E.
	Team Lead		Regional Manager
TITLE:	Building & Construction	TITLE:	Building & Construction
SIGNATURE:		SIGNATURE:	
DATE:	03/14/25	DATE:	03/14/25

BAJ

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample(s) tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

TEST REPORT FOR FLEETWOOD WINDOWS & DOORS

Report No.: S0187.02-303-44 R1

Date: 03/06/25

SECTION 2

SUMMARY OF TEST RESULTS

TITLE	RESULTS
AAMA/WDMA/CSA 101/I.S.2/A440-22	Class LC PG – 50 Size Tested: 5486 mm X 3708 mm (215.98" X 145.98")
Design Pressure	±2400 Pa (±50.13 psf)
Negative Design Pressure	-2400 Pa (-50.13 psf)
Air Infiltration	0.71 L/s/m ² (0.15 cfm/ft ²)
Air Exfiltration	0.99 L/s/m ² (0.21 cfm/ft ²)
Water Penetration Resistance Test Pressure	360 Pa (7.52 psf)

SECTION 3

TEST SPECIFICATIONS/METHODS

The specimens were evaluated in accordance with the following:

AAMA/WDMA/CSA 101/I.S.2/A440:22, *North American Fenestration Standard/Specification for Windows, Doors, and Skylights*

The following test methods were used during testing:

ASTM E283/E283M-19, *Standard Test Method for Determining Rate of Air Leakage Through Exterior Windows, Skylights, Curtain Walls, and Doors Under Specified Pressure Differences Across the Specimen*

ASTM E330/E330M-14(2021), *Standard Test Method for Structural Performance of Exterior Windows, Doors, Skylights and Curtain Walls by Uniform Static Air Pressure Difference*

ASTM E547-00(2016), *Standard Test Method for Water Penetration of Exterior Windows, Skylights, Doors, and Curtain Walls by Cyclic Static Air Pressure Difference*

ASTM E987-88(2017), *Standard Test Methods for Deglazing Force of Fenestration Products*

ASTM E2068-00(2022), *Standard Test Method for Determination of Operating Force of Sliding Windows and Doors*

ASTM F842-17, *Standard Test Methods for Measuring the Forced Entry Resistance of Sliding Door Assemblies, Excluding Glazing Impact*

TEST REPORT FOR FLEETWOOD WINDOWS & DOORS

Report No.: S0187.02-303-44 R1

Date: 03/06/25

SECTION 4

MATERIAL SOURCE/INSTALLATION

Test specimen was provided by the client. Representative samples of the test specimen will be retained by Intertek B&C for a minimum of two years from the test completion date.

The specimen was installed into a Douglas-Fir lined steel test buck. The rough opening allowed for a 1/4" shim space and the exterior perimeter of the specimen was sealed to the test buck. The installation of the tested product was performed by the client.

LOCATION	ANCHOR DESCRIPTION	ANCHOR SPACING
Through the frame	#8 X 2" SMS Screws	6 rows of screws 8" from the corners and 18" on center of the head and jambs.
Through the frame	#6 X 1-1/2" SMS Screws	8" from the comers and 16" on center through the sill.

SECTION 5

EQUIPMENT

The following equipment was utilized to apply Forced Entry Resistance (FER) loading in accordance with ASTM F842:

EQUIPMENT	ASSET NUMBERS	CALIBRATION DUE DATE
Stopwatch	INT03845	5/8/25
Load Cells	63066	10/2/25
	63067	10/3/25
Force Gauge	005555	8/22/25

A FER tool kit containing the following tools was also utilized:

- 24 gauge 0.024" thick x 0.78" wide x 3.5" long stainless-steel spatula/putty knife/non-cutting tool, unwrapped
- 6" Phillips head screwdriver [unpowered, 6 in max]
- 6" standard slot-type pliers [max 6 to 7 in (150 to 175 mm) overall length]
- Black annealed 16-gauge straight wire.

TEST REPORT FOR FLEETWOOD WINDOWS & DOORS

Report No.: S0187.02-303-44 R1

Date: 03/06/25

SECTION 6

LIST OF OFFICIAL OBSERVERS

NAME	COMPANY
Corey Jones	Fleetwood Windows & Doors
Benjamin Johns	Intertek B&C

SECTION 7

TEST SPECIMEN DESCRIPTION

Product Type: Sliding Door

Series/Model: 4070 – T HP Sliding Glass Door

Product Size:

Test Specimen #1

OVERALL, AREA:	WIDTH		HEIGHT	
	millimeters	inches	millimeters	inches
20.34 m ² (218.96 ft ²)				
Overall size	5486	215.98	3708	145.98
Exterior operable panel right side (outside view)	1861	73.27	3661	144.125
Middle Operable Panel	1845	72.64	3661	144.125
Interior operable panel left side (outside view)	1861	73.27	3661	144.125

Frame Construction:

MEMBER	MATERIAL	DESCRIPTION
Head	Aluminum	Extruded
Sill	Aluminum	Extruded
Jambs	Aluminum	Extruded

	JOINERY TYPE	DETAIL
All corners	Butt	Attached with screws

TEST REPORT FOR FLEETWOOD WINDOWS & DOORS

Report No.: S0187.02-303-44 R1

Date: 03/06/25

Panel Construction:

MEMBER	MATERIAL	DESCRIPTION
Top rail	Aluminum	Extruded
Bottom rail	Aluminum	Extruded
Stiles	Aluminum	Extruded

	JOINERY TYPE	DETAIL
All corners	Butt	Attached with screws

Reinforcement: *No reinforcement was utilized.*

Weatherstripping:

DESCRIPTION	QUANTITY	LOCATION
Pile gasket	1	At the right meeting stile of the middle panel. (inside view)
Rubber gasket	1	At the right meeting stile of the middle panel.
Pile gasket	1	At the right interlock on the middle panel (outside view)
Pile gasket	1	At the right interlock of the left panel (inside view)
Rubber gasket	1	At the right meeting stile of the left panel. (inside view)
Pile gasket	1	At the right meeting stile of the left panel. (inside view)
Pile gasket	12 rows	On the sill of the frame.
Pile gasket	6 Rows	On the head of the frame
Q-lon bulb gasket	4	2 rows on both jambs of the frame.

TEST REPORT FOR FLEETWOOD WINDOWS & DOORS

Report No.: S0187.02-303-44 R1

Date: 03/06/25

Glazing:

GLASS TYPE	SPACER TYPE	INTERIOR LITE	EXTERIOR LITE	GLAZING METHOD
1.25" IG	Cardinal black XL spacer	1/4" Tempered	1/4" Tempered	Dry glazed.

LOCATION	QUANTITY	DAYLIGHT OPENING		GLASS BITE
		millimeters	inches	
All panels	3	1725 x 3495	67.91 x 137.60	9/16"

Drainage:

METHOD	SIZE	QUANTITY	LOCATION
Weep hole	1" wide by 3/16" high	4	1 @ 9" 1 @ 70" on center from the right jamb on the sill. 1 @ 9" 1 @ 70" on center from the left jamb on the sill.

Hardware:

DESCRIPTION	QUANTITY	LOCATION
Lock	2	1 @ 46" on center from the top of the sill on the left stile of the left panel. (inside view) 1 @ 46" on center from the top of the sill on the right stile of the right panel. (inside view)
Wheel assembly	6	2 on the bottom corners of all 3 panels

TEST REPORT FOR FLEETWOOD WINDOWS & DOORS

Report No.: S0187.02-303-44 R1

Date: 03/06/25

SECTION 8

TEST RESULTS

The temperature during testing was (62°F). The results are tabulated as follows:

Test Specimen:

TITLE OF TEST	RESULTS	ALLOWED	NOTE
Operating Force, per ASTM E2068	Initiate Motion: 80 N (18.0 lbf) Maintain Motion: 78 N (17.5 lbf) Locks: 37.81 N (8.50 lbf)	155 N (35.0 lbf) max 155 N (35.0 lbf) max Report only	
Air Leakage, Infiltration per ASTM E283 at 75 Pa (1.57 psf)	<0.71 L/s/m ² (<0.15 cfm/ft ²)	1.5 L/s/m ² (0.3 cfm/ft ²) max.	1, 2
Air Leakage, Exfiltration per ASTM E283 at 75 Pa (1.57 psf)	<0.99 L/s/m ² (<0.21 cfm/ft ²)	1.5 L/s/m ² (0.3 cfm/ft ²) max.	1, 2
Water Penetration, per ASTM E547 at 360 Pa (7.52 psf)	Pass	No leakage	3
Uniform Load Deflection, per ASTM E330 Deflections taken at the right meeting stile +2520 Pa (+52.63 psf) -2520 Pa (-52.63 psf)	20.57 mm (0.81") 20.83 mm (0.82")	Report only Report only	4,5,6,7
Uniform Load Structural, per ASTM E330 Permanent set taken at the right meeting stile +3600 Pa (+75.19 psf) -3600 Pa (-75.19 psf)	<0.26 mm (<0.01") <0.26 mm (<0.01")	14.48 mm (0.57") max. 14.48 mm (0.57") max.	4,5,6,7
Forced Entry Resistance, per ASTM F842, Type: A - Grade: 10	Pass	No entry	
Deglazing, per ASTM E987 Operating direction, 320 N (70 lbf)	Pass	Meets as stated	

TEST REPORT FOR FLEETWOOD WINDOWS & DOORS

Report No.: S0187.02-303-44 R1

Date: 03/06/25

Test Specimen:

TITLE OF TEST	RESULTS	ALLOWED	NOTE
Remaining direction, 230 N (50 lbf)	Pass	Meets as stated	

Note 1: The tested specimen meets (or exceeds) the performance levels specified in AAMA/WDMA/CSA 101/I.S.2/A440 for air leakage resistance.

Note 2: Test Date 02/20/25 / Time: 2:00 PM (Air Note Only)

Note 3: Without an insect screen.

Note 4: The client opted to start at a pressure higher than the minimum required. Test results are reported under Optional Performance.

Note 5: The deflections reported are not limited by AAMA/WDMA/CSA 101/I.S.2/A440 for this product designation. The deflection data is recorded in this report for special code compliance and information only.

Note 6: Loads were held for 10 seconds.

Note 7: Tape and film were used to seal against air leakage during structural testing. In our opinion, the tape and film did not influence the results of the test.

TEST REPORT FOR FLEETWOOD WINDOWS & DOORS


Report No.: S0187.02-303-44 R1

Date: 03/06/25

SECTION 9

LOCATION OF AIR SEAL

The air seal between the test specimen and the test wall is detailed below. The seal is made of foam weatherstripping and is attached to the edge of the test specimen buck. The test specimen buck is placed against the test wall and clamped in place, compressing the weatherstripping and creating a seal.



TEST REPORT FOR FLEETWOOD WINDOWS & DOORS

Report No.: S0187.02-303-44 R1

Date: 03/06/25

SECTION 10

CONCLUSION

The specimens tested successfully met the performance requirements for the following rating:

TEST SPECIMEN	TITLE	SUMMARY OF RESULTS
1	AAMA/WDMA/CSA 101/I.S.2/A440:22	Class LC PG – 50 Size Tested: 5486 mm X 3708 mm (215.98" X 145.98")

SECTION 11

DRAWINGS

The test specimen drawings have been reviewed by Intertek B&C and are representative of the test specimen reported herein. Test specimen construction was verified by Intertek B&C per the drawings included in this report. Any deviations are documented herein or on the drawings.

Note: Complete drawings packet on file with Intertek B&C.

TABLE OF CONTENTS

- SHEET NO.
 1. GENERAL NOTES, DESIGN LOADS, FRAME ANCHOR TABLE AND SPECIMEN ELEVATION
 2. DETAILS
 3. DETAILS
 4. BILL OF MATERIALS

TEST SPECIMEN

1. SERIES / MODEL: 4070-T
 2. PRODUCT TYPE: MULTI-SLIDE DOOR WITH 7/8" SILL

GENERAL NOTES

1. BUCKING OPENINGS & BUCKING FASTENERS MUST BE PROPERLY DESIGNED & INSTALLED TO TRANSFER LOADS TO THE STRUCTURE AND TO BE REVIEWED BY BUILDING OFFICIAL.
 2. ALL HARDWARE & FASTENERS SHALL BE IN ACCORDANCE WITH THESE DRAWINGS & MAY NOT VARY UNLESS SPECIFICALLY MENTIONED ON THE DRAWINGS.
 3. MATERIALS, INCLUDING BUT NOT LIMITED TO STEEL SCREWS, THAT COME INTO CONTACT WITH OTHER DISSIMILAR MATERIALS SHALL MEET THE REQUIREMENTS OF AAMA AND BUILDING CODE.

SPECIFICATIONS

1. NAFS-22

CORNERS CONSTRUCTION

1. **FRAME CORNER:** THE JAMBS ARE BUTTED TO THE HEAD AND SILL AND ATTACHED WITH #10 PHP SCREWS.
 2. **PANEL CORNER:** THE HORIZONTAL RAILS ARE BUTTED TO THE VERTICALS AND ATTACHED WITH #8 FHP SCREWS.

GLAZING

LITE 1: 1.25" CLEAR 6MM-T, 0.75 AIR, CLEAR 6MM-T
 LITE 2: 1.25" CLEAR 6MM-T, 0.75 AIR, CLEAR 6MM-T
 LITE 3: 1.25" CLEAR 6MM-T, 0.75 AIR, CLEAR 6MM-T
 ALL GLAZING SEALANT SIKASIL SG-10
 1/4" X 1/4" X 12" BEAD FROM EACH CORNER OF INNER FLANGE OF PANEL
 FOR PANEL HEIGHTS OVER 8 FT. TALL RECOMMENDED AN ADDITIONAL 24" OF SEALANT HALFWAY UP PANEL.

SILLPAN DRAIN SPACING

8" FROM ENDS, 60" SPACING FROM LEFT, IF SPACING <60" TAKE REMAINING SPACE AND DIVIDE BY 2.
 WEEP SIZE = 1" X 3/16", CUT ACROSS ENTIRE TRACK DEPTH.

*FRAME ANCHOR REQUIREMENTS TABLE			
OPENING TYPE (SUBSTRATE)	FRAME TO OPENING FASTENER TYPE	MINIMUM EMBEDMENT	MINIMUM EDGE DIST.
2X_ WOOD FRAME OR BUCK	(1) NO. 8 SMS SCREW	1 1/2"	3/4"
MIN. 18 GA. 33 KSI STEEL STUD	(1) NO. 8 SMS SCREW	FULL	3/8"
CMU/CONCRETE	(2) 3/16" CONCRETE SCREWS	1 1/4"	2 5/8"


(1) SMS SCREWS
 (2) CONCRETE SCREWS SHALL BE 3/16" ITW TAPCON

ANCHORING

SCREW: MIN. EMBEDMENT OF 0.75", 2x PER TRACK ANCHOR LOCATION
 HEAD: 8" FROM ENDS, 18" O.C.
 JAMBS: 8" FROM ENDS, 18" O.C.
 SILL (OVER 45 PSF): 8" FROM ENDS, 60" O.C. USE #6X1.5" FHP

PANEL & PANEL DLO: WIDTH X HEIGHT

PANEL 1: 73.19" X 144.125" DLO 1: 67.88" X 137.75"
 PANEL 2: 72.75" X 144.125" DLO 2: 67.75" X 137.75"
 PANEL 3: 73.19" X 144.125" DLO 3: 67.88" X 137.75"



	Report #:	S0187.02-303-44
	Date:	03/04/25
	Verified by:	<i>[Signature]</i>

COMMENTS	DRAWN BY	DATE	REVISIONS	DATE:	DRAWN BY:	JOB NUMBER:
				12/19/24	CJ	581121

MATERIAL: 4070-T 7/8" Sill
 CUSTOMER: FLEETWOOD WINDOWS AND DOORS
 JOB NAME: 4070-T 7/8" Sill Cert Testing

1 FLEETWOOD WAY
 CORONA, CA 92879
 www.fleetwoodusa.com


FLEETWOOD
 WINDOWS & DOORS

SCALE : 3/4" = 1'
 DRAWING NO. : 1
 SHEET : 1 OF 4

1 4070-T HEAD
SCALE: FULL SIZE

EXTERIOR


2 4070-T SILL
SCALE: FULL SIZE



intertek
Total Quality Assured.

Report #: S0187.02-303-44
Date: 03/04/25
Verified by: *Erin J. Baker*

MATERIAL: 4070-T 7/8" Sill		DATE: 1/8/25	COMMENTS
CUSTOMER: FLEETWOOD WINDOWS AND DOORS		DRAWN BY: CJ	DRAWN BY
JOB NAME: 4070-T 7/8" Sill Cert Testing		DATE	DATE
		REVISIONS	REVISIONS
		1	1
		2	2
		3	3
		4	4
		5	5
		6	6
		7	7
		8	8
		9	9
		10	10
		11	11
		12	12
		13	13
		14	14
		15	15
		16	16
		17	17
		18	18
		19	19
		20	20
		21	21
		22	22
		23	23
		24	24
		25	25
		26	26
		27	27
		28	28
		29	29
		30	30
		31	31
		32	32
		33	33
		34	34
		35	35
		36	36
		37	37
		38	38
		39	39
		40	40
		41	41
		42	42
		43	43
		44	44
		45	45
		46	46
		47	47
		48	48
		49	49
		50	50
		51	51
		52	52
		53	53
		54	54
		55	55
		56	56
		57	57
		58	58
		59	59
		60	60
		61	61
		62	62
		63	63
		64	64
		65	65
		66	66
		67	67
		68	68
		69	69
		70	70
		71	71
		72	72
		73	73
		74	74
		75	75
		76	76
		77	77
		78	78
		79	79
		80	80
		81	81
		82	82
		83	83
		84	84
		85	85
		86	86
		87	87
		88	88
		89	89
		90	90
		91	91
		92	92
		93	93
		94	94
		95	95
		96	96
		97	97
		98	98
		99	99
		100	100
		101	101
		102	102
		103	103
		104	104
		105	105
		106	106
		107	107
		108	108
		109	109
		110	110
		111	111
		112	112
		113	113
		114	114
		115	115
		116	116
		117	117
		118	118
		119	119
		120	120
		121	121
		122	122
		123	123
		124	124
		125	125
		126	126
		127	127
		128	128
		129	129
		130	130
		131	131
		132	132
		133	133
		134	134
		135	135
		136	136
		137	137
		138	138
		139	139
		140	140
		141	141
		142	142
		143	143
		144	144
		145	145
		146	146
		147	147
		148	148
		149	149
		150	150
		151	151
		152	152
		153	153
		154	154
		155	155
		156	156
		157	157
		158	158
		159	159
		160	160
		161	161
		162	162
		163	163
		164	164
		165	165
		166	166
		167	167
		168	168
		169	169
		170	170
		171	171
		172	172
		173	173
		174	174
		175	175
		176	176
		177	177
		178	178
		179	179
		180	180
		181	181
		182	182
		183	183
		184	184
		185	185
		186	186
		187	187
		188	188
		189	189
		190	190
		191	191
		192	192
		193	193
		194	194
		195	195
		196	196
		197	197
		198	198
		199	199
		200	200
		201	201
		202	202
		203	203
		204	204
		205	205
		206	206
		207	207
		208	208
		209	209
		210	210
		211	211
		212	212
		213	213
		214	214
		215	215
		216	216
		217	217
		218	218
		219	219
		220	220
		221	221
		222	222
		223	223
		224	224
		225	225
		226	226
		227	227
		228	228
		229	229
		230	230
		231	231
		232	232
		233	233
		234	234
		235	235
		236	236
		237	237
		238	238
		239	239
		240	240
		241	241
		242	242
		243	243
		244	244
		245	245
		246	246
		247	247
		248	248
		249	249
		250	250
		251	251
		252	252
		253	253
		254	254
		255	255
		256	256
		257	257
		258	258
		259	259
		260	260
		261	261
		262	262
		263	263
		264	264
		265	265
		266	266
		267	267
		268	268
		269	269
		270	270
		271	271
		272	272
		273	273
		274	274
		275	275
		276	276
		277	277
		278	278
		279	279
		280	280
		281	281
		282	282
		283	283
		284	284
		285	285
		286	286
		287	287
		288	288
		289	289
		290	290
		291	291
		292	292
		293	293
		294	294
		295	295
		296	296
		297	297
		298	298
		299	299
		300	300
		301	301
		302	302
		303	303
		304	304
		305	305
		306	306
		307	307
		308	308
		309	309
		310	310
		311	311
		312	312
		313	313
		314	314
		315	315
		316	316
		317	317
		318	318
		319	319
		320	320
		321	321
		322	322
		323	323
		324	324
		325	325
		326	326
		327	327
		328	328
		329	329
		330	330
		331	331
		332	332
		333	333
		334	334
		335	335
		336	336
		337	337
		338	338
		339	339
		340	340
		341	341
		342	342
		343	343
		344	344
		345	345
		346	346
		347	347
		348	348
		349	349
		350	350
		351	351
		352	352
		353	353
		354	354
		355	355
		356	356
		357	357
		358	358
		359	359



1 4070-T LOCK JAMB
SCALE: FULL SIZE

2 4070-T INTERLOCKERS
SCALE: FULL SIZE

















2 4070-T INTERLOCKERS
SCALE: FULL SIZE

5 4070-T LOCK JAMB
SCALE: FULL SIZE






intertek
Total Quality. Assured.

Report #: S0187.02-303-44
Date: 03/04/25
Verified by: *Benjamin Adams*

MATERIAL: 4070-T 7/8" Sill		DATE: 1/8/25	REVISIONS	DATE	DRAWN BY	COMMENTS
CUSTOMER: FLEETWOOD WINDOWS AND DOORS		DATE: 1/8/25			CJ	
JOB NAME: 4070-T 7/8" Sill Cert Testing		JOB NUMBER: 581121				
<p>1 FLEETWOOD WAY CORONA, CA 92879 www.fleetwoodusa.com</p> <p>FLEETWOOD WINDOWS & DOORS</p>						
SCALE: 1" = 1'						
DRAWING NO.: 3						
SHEET: 3 OF 4						



ITEM #	PART	ITEM DESCRIPTION	MANUFACTURER/NOTES
PARTS			
1	4727	BLOCK HEAD	6063-T6 ALUMINUM EXTRUSION
2	4702	INTERMEDIATE HEAD	6063-T6 ALUMINUM EXTRUSION
3	4728	BLOCK JAMB	6063-T6 ALUMINUM EXTRUSION
4	4704	INTERMEDIATE JAMB	6063-T6 ALUMINUM EXTRUSION
5	4748	SILL	6063-T6 ALUMINUM EXTRUSION
6	4750	7/8" SILL BOTTOM RAIL	6063-T6 ALUMINUM EXTRUSION
7	4709	TOP RAIL	6063-T6 ALUMINUM EXTRUSION
8	4742	LEAD STILE	6063-T6 ALUMINUM EXTRUSION
9	4737	HP SLIDING INTERLOCKER	6063-T6 ALUMINUM EXTRUSION
10	4711	FIXED INTERLOCKER	6063-T6 ALUMINUM EXTRUSION
11	4705	JAMB FILLER	6063-T6 ALUMINUM EXTRUSION
12	4735	1.25" GLASS STOP	6063-T6 ALUMINUM EXTRUSION
SEALS & SEALANTS			
13	25912	SMALL FIN SEAL .200	AMESBURY (20027045BKGB)
14	25031	Bulb Vinyl-Large (EPDM 70 Durometer, ASTM C864)	TREMCO, #TX19638E
15	27538	MOHAIR 27027045BKGB	AMESBURY, 27027045BKGB
16	19118	SMALL FIN SEAL .230	AMESBURY (23027045BKGB)
17	25757	Q-Lon Foam Seal	SCHLEGEL, Q-Lon Q200T270
18	26046	FLEXIBLE VINYL AIR BARRIER	RYKO
19	25199	Mini Bulb Vinyl (EPDM 70 Durometer, ASTM C864)	TREMCO, TX20801E
MISCELLANEOUS			
20	25065	14.6mm X 10.2mm - I-STRUT	TECHNOFORM, 259900
21	TBD	SILLPAN	ALUMINUM
22	27313	4" X 3/16" X 1" SETTING BLOCK	AS REQ'D
23	23006	STAINLESS STEEL TRACK 9/16" (SLIDING DOORS) .035"	HAAG & ASSOCIATES, FW-1020
24	23025	PVC TRACK JOINER	RYKO, R10882
25	25942	BRUSH AIR BARRIER	D&B, 233-100



Intertek Report #: S0187.02-303-44
 Total Quality Assured. Date: 03/04/25
 Verified by: *[Signature]*

COMMENTS				
DRAWN BY				
DATE				
REVISIONS				
DATE:	1/8/25			
DRAWN BY:	CJ			
JOB NUMBER:	581121			
MATERIAL:	4070-T 7/8" Sill			
CUSTOMER:	FLEETWOOD WINDOWS AND DOORS			
JOB NAME:	4070-T 7/8" Sill Cert Testing			
<p>1 FLEETWOOD WAY CORONA, CA 92879 www.fleetwoodusa.com</p> <p>FLEETWOOD WINDOWS & DOORS</p>				
SCALE: 1" = 1'				
DRAWING NO.: 4				
SHEET: 4 OF 4				

TEST REPORT FOR FLEETWOOD WINDOWS & DOORS

Report No.: S0187.02-303-44 R1

Date: 03/06/25

SECTION 12

REVISION LOG

REVISION #	DATE	PAGES	REVISION
0	03/06/25	N/A	Original Report Issue
1	03/14/25	3,4 & 7	Change the summary psf on the water portion to 7.52 psf, add correct anchor details page 4 and fix verbiage on the roller assembly hardware page 7